

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
19 June 2003 (19.06.2003)

PCT

(10) International Publication Number  
**WO 03/049621 A1**

(51) International Patent Classification<sup>7</sup>: **A61B 17/04**

(21) International Application Number: PCT/US02/39151

(22) International Filing Date: 6 December 2002 (06.12.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
10/004,817 7 December 2001 (07.12.2001) US

(71) Applicant: **ABBOTT LABORATORIES** [US/US];  
D-377 AP6A-1, 100 Abbott Park Road, Abbott Park, IL  
60064-6008 (US).

(72) Inventors: **DANA, Mike**; 1664 Brookvale Dr, Apt 1, San  
Jose, CA 95129 (US). **GEORGE, Rob**; 15123 Chelsea  
Drive, San Jose, CA 95124 (US). **GROSS, T., Daniel**; 200  
Kimble Ave, Los Gatos, CA 95030 (US). **MARTHALER,**  
**Maurice**; 2075 McDaniel Ave, San Jose, CA 95128 (US).

**MA, Dawn**; 1678 Canyon View Dr, San Jose, CA 95132  
(US). **SWETT, Jim**; 1006 Eve Ln, Livermore, CA 94550  
(US).


(74) Agents: **TWAROWSKI, Joseph, A.** et al.; D-377  
AP6A-1, 100 Abbott Park Road, Abbott Park, IL  
60064-6008 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,  
SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC,  
VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK,  
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: SURGICAL SUTURE PASSER AND TRIMMER



(57) Abstract: A suture trimmer, the suture trimmer including a shaft having a first end, a second end and a bore extending axially therebetween, the shaft having an opening formed in the side adjacent the distal end. A fitting is on the distal end of the shaft, the fitting having an aperture formed therethrough, the aperture axially aligned with the bore of the lumen and in communication with the opening formed in the shaft. The suture trimmer further including a actuating device, the actuating device coupled to a cutting member slidably disposed within the bore of the shaft, the cutting member configured to be moved between a first position and a second position, when disposed in the second position the cutting member closes the opening formed in the side of the shaft.



WO 03/049621 A1



**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

5

## SURGICAL SUTURE PASSER AND TRIMMER

**Field Of The Invention**

The present invention relates generally to surgical devices and methods. More particularly, the present invention relates to the construction and use of devices for advancing surgical knot(s) and trimming the ends of the suture adjacent to the knot(s). Such a device is to be referred to as a "suture trimmer", as used through the appended specification.

**Background Of The Invention**

The closing of incision and wounds using suture is a preferred technique of surgeons and many other physicians. While other techniques are now available such as stapling, the use of "tissue glues," and the use of collagen for closing vascular punctures, the use of suture is often preferred because it provides a reliable and tight closure of any wound. Additionally, if a suture is to fail, the surgeon will know immediately, this is unlike many of the other devices listed above which may not fail until some time after the procedure.

While the suturing of a wound is a relatively straight forward procedure in most open surgical procedures, placement and tying of sutures in laprascopic and other minimally invasive procedures can be problematic. In order to provide for suturing under such circumstances, a variety of devices have been developed for the remote placement and tying of suture through cannulas under video observation. Usually, a sliding knot will be formed in a suture loop, a tool known as a "knot pusher" such as that shown in U.S. Patent No. 5,797,929 the entirety of which is hereby incorporated by reference, is utilized to advance and position the knot and tighten the loop of suture.

Such knot pushing devices may also be utilized in recently developed techniques for the remote suturing of vascular punctures. Punctures may be formed in the femoral or other arteries to provide vascular access for performing angioplasty and other vascular procedures. Such techniques are described in U.S. Patent No. 5,417,699 and U.S. Patent No. 5,527,322 the entirety of which are hereby incorporated by reference. Such methods result in the placement of a suture loop through tissue on opposite sides of the vascular puncture. Two free ends of the suture loop are brought out through a tissue tract leading to the puncture, and the ends may be externally tied by the treating physician. Alternatively, a knot forming device such as that shown in U.S. Patent No. 6,171,317, the entirety of which is hereby incorporated by reference, may be utilized to tie a knot.

5 Through the use of a knot pusher, such as that shown and described in U.S. Patent No. 5,797,929, the entirety of which is hereby incorporated by reference, the knot may be advanced through the tissue tract so that it lies directly over the adventitial wall of the blood vessel.

After the knot has been advanced over the adventitial wall of the blood vessel and tightened, the excess suture must be cut away. Typically, a surgeon may utilize a scalpel or a  
10 pair of scissors to cut the suture ends just below the exterior surface of the patient's skin.

A concern with this method is that by leaving lengths of suture within the wound may lead to irritation of the incision. More significantly, a relatively long suture end, extending from the knot at the vessel repair to the skin level, may act as a "wick" for infective microorganisms which may be present at skin level. The wick would provide a conduit for these microorganisms  
15 to travel from the skin surface to the vessel repair, thereby leading to infection. Many times a surgeon cannot easily shorten this cut length because the location of the knot is well below the patient's tissue and is not readily visible, therefore they can only shorten the suture to the point that they can visually see. Further still, many surgical procedures are moving away from being open and toward being minimally invasive wherein the procedure is performed within a small  
20 opening formed in the patient's tissue. As described above, many times the surgeon cannot see the vessel which they are trying to close with the suture.

Therefore there is a need for a device that will enable a surgeon to advance a knot and trim the excess suture from the knot without having to visually see the knot.

## 25 **Summary Of The Invention**

In one aspect of the invention there is provided a suture trimmer, the suture trimmer including a shaft having a first end, a second end and a bore extending axially therebetween, the shaft having an opening formed in the side adjacent the distal end. A fitting disposed on the distal end of the shaft, the fitting having an aperture formed therethrough, the aperture axially  
30 aligned with the bore of the lumen and in communication with the opening formed in the shaft. The suture trimmer further includes a housing disposed on the proximal end of the shaft, the housing including a lever and biasing device, the lever coupled to a cutting member slidably disposed within the bore of the shaft, the cutting member configured to be moved between a first position and a second position, when disposed in the second position the cutting member closes  
35 the opening formed in the side of the shaft.

In another aspect of the invention there is provided a method for closing a suture loop, the method including the steps of tensioning a suture loop, the suture loop disposed within a

5 patient and having two free ends and a knot disposed on one of the free ends. The method further includes disposing the two free ends of the suture through a suture trimming device. The method may further include the step of advancing a distal end of the suture trimming device to contact the knot and advance the knot to close the suture loop while holding at least one end of the suture, and activating a cutting member within the suture trimmer to cut the two free ends of  
10 the suture adjacent to the knot.

### Detailed Description Of The Drawings

The objects and advantages of the invention will become apparent from the following detailed description of preferred embodiments thereof in connection with the accompanying  
15 drawings in which like numerals designate like elements and in which:

Figure 1 is a isometric view of an exemplary embodiment of a suture trimmer in accordance with the present invention;

20 Figure 2 is a partial cut-away isometric view of an exemplary embodiment of the suture trimmer in accordance with the present invention;

Figure 3 is a partial cut-away isometric view of an exemplary embodiment of the suture trimmer in accordance with the present invention wherein the cutting member has been  
25 deployed;

Figure 4 is a isometric view of an exemplary embodiment of a fitting in accordance with the present invention;

30 Figure 5 is a cross-sectional view of the shaft, fitting, and cutting member of the suture cutter in accordance with the present invention;

Figure 6 is a isometric view of a suture snare in accordance with the present invention;

35 Figure 7 is a isometric view of the suture trimmer in accordance with the present invention wherein two free suture ends are disposed through the suture snare;

5           Figure 8           is an isometric view of the suture trimmer in accordance with the present invention illustrating the two free suture ends as disposed through fitting and exiting through an opening formed in the shaft;

          Figure 9           is an isometric view of the suture trimmer according to the present  
10       invention wherein the tip of the suture trimmer is being utilized to advance at least one knot formed in the two free ends of the suture; and

          Figure 10          is an isometric view of the suture trimmer in accordance with the present invention wherein the cutting member has been deployed to cut the two free ends of the suture.

15

### **Detailed Description Of A Preferred Embodiment**

          In accordance with the present invention there is provided a suture trimmer, the suture trimmer may be utilized by physicians in any of a variety of surgical procedures where suture  
20       loop has been formed in tissue to close an incision or wound, or for any other purpose. A slidable knot will be formed in the loop, and the suture trimmer is used to engage and advance the knot over a free end of the suture to close the loop. The knot can then be tightened by pulling on the other free end of the suture. The free ends of the suture may then be trimmed adjacent to the knot by activating the cutting member of the suture trimmer.

25           The suture trimmer in accordance with the present invention comprises an elongated, narrow diameter shaft suitable for use in remote procedures performed through percutaneous tissue punctures, such as vascular closures, laproscopic and other minimally invasive procedures and the like. Thus, the shaft of the suture trimmer may be embodied in many lengths to accommodate the various procedures for which the device may be utilized. The diameter of the  
30       shaft will be sufficiently small to facilitate the introduction through access sheaths, trocars, and the like, as well as punctures through the tissue of a patient's body, herein referred to as a "tissue tract." Typically the diameter of the shaft will range from about 4 French to about 10 French, more preferably the diameter of the shaft may range from about 6 French to about 8 French. The distal end of the shaft configured to engage and advance a slidable knot. A housing may be  
35       provided on the proximal end of the shaft wherein the housing forms a handle and retains a mechanism for activating the cutting member disposed in the shaft.

5           It shall be appreciated that although the suture trimmer has been described as being utilized in minimally invasive procedures, it is contemplated that the suture trimmer may be utilized for many open procedures that utilize suture to close vessels or wounds.

          In a preferred embodiment a fitting will be provided at the distal end of the shaft. The fitting is preferably formed of a relatively hard material to firmly engage the knot and permit  
10   smooth advancement of the knot. The fitting is typically a cylindrical element having a flat or slightly convex or concave front face. The fitting preferably has a diameter equal to or less than the diameter of the shaft. The fitting will further included an aperture formed through an axis thereof and in communication with an opening formed in the side of the shaft. The free ends of the suture may be drawn through the aperture and opening through the use of a suture snare.  
15   Alternatively, the fitting may include a groove in communication with the aperture and the opening formed in the shaft. The free ends of the suture may be received in the groove and drawn therethrough, wherein, the free ends of the suture extend from the opening formed in the shaft, thereby eliminating the need for a snare. A locking mechanism may be deployed to retain the suture within the groove. The free ends of the suture extending from the opening formed in  
20   the shaft enable the tensioning of the knot after advancement of the knot. In an alternative embodiment, the structure of the fitting described herein may be integral with or formed from the shaft material such that a separate fitting piece can be eliminated from the assembly of the suture trimmer.

          The shaft of the suture trimmer in accordance with the present invention is preferably  
25   rigid, typically being formed from of a bio-compatible material such as metal or plastic. Suitable metals include stainless steel, gold plated metals, silver plated metals, platinum or platinum plated metals, or titanium. It shall be understood that other metals may be utilized if an appropriate bio-compatible coated was applied thereto. Suitable plastics include polycarbonate, polyvinyl chloride (PVC), nylon, or similar plastics. As will be described in greater detail  
30   below, the shaft may be formed of more than one component. It is further contemplated that the shaft may be constructed to provide a degree of flexibility which will enable the device to be utilized in a greater number of surgical procedures.

          The housing may be constructed of a bio-compatible material such as metal or plastic. Suitable metals include stainless steel, gold plated metals, silver plated metals, platinum or  
35   platinum plated metals, or titanium. It shall be understood that other metals may be utilized if an appropriate bio-compatible coated was applied thereto. Suitable plastics include polycarbonate, polyvinyl chloride (PVC), nylon, or similar plastics. In a preferred embodiment the housing is constructed of plastic.

5 Referring now to Figure 1 there is shown an exemplary embodiment of the suture trimmer in accordance with the present invention. As shown in Figure 1, the suture trimmer 10 comprises a shaft assembly 21, a housing 30, a fitting 50, and a suture snare 90. Each of which will be described in greater detail below with respect to the appropriate figures.

Referring now to Figure 2, there is shown a partial cut-away view of an exemplary  
10 embodiment of the suture trimmer 10 in accordance with the present invention. As shown, the shaft assembly 21 comprises an outer shaft 20, a cutting member 60 slidably disposed therein and a fitting 50 disposed on the distal tip. Referring now to Figure 1, the outer shaft 20 further includes an opening 23 formed in the side thereof adjacent to the distal tip. The proximal end of the shaft assembly 21 is received within a housing 30. The housing further including a biasing  
15 member 65 and a cutting member actuating device 40. The biasing member 65 is operatively coupled to the cutting member 60, thereby retaining the cutting member in a retracted position. The cutting member actuating device 40 advances the cutting member 60 within the bore of the shaft, wherein the cutting member extends to cover the opening formed in the side of the shaft and to sever suture projecting therefrom.

As shown in Figure 5, the cutting member 60 may comprise a semi-circular or circular  
20 member disposed about the protrusion 54 of the fitting 50. Referring now to Figure 2, the cutting member 60 includes a proximal end 62 and a distal end 61, the distal end being configured to sever suture. As shown in Figure 2, a bushing 67 is disposed about the proximal end 62 of the cutting member 60. The bushing 67 retains the biasing member 65 within the  
25 housing 50. The bushing further includes at least one protrusion 68 extending therefrom and perpendicular to the axis of the shaft. The protrusion 68 is configured to engage the cutting member actuating device 40 disposed within the housing 50 as shown in Figure 3.

Referring now to Figure 3 there is shown the suture trimmer 10 in accordance with the present invention wherein the cutting member actuating device 40 has been actuated, thereby  
30 advancing the distal end of the cutting member across the opening 23 of the shaft 21. As shown in Figures 2 and 3, the cutting member actuating device 40 has a proximal end and a distal end. The proximal end being configured to engage the protrusions 68 extending from the bushing 67. The distal portion of the actuating device 40 may include a depressed or sculpted area configured to receive a user's finger, thereby providing a more positive grip on the actuating  
35 device. The actuating device 40 further includes a pivot pin 45. The pivot pin 45 is adapted to engage a portion 35 of the main housing 30, wherein the portion 35 of the main housing rotatably receives the pivot pin 45 thereby allowing the actuating device 40 to pivot about the portion 35.



5 Referring now to Figure 4, there is shown an exemplary embodiment of the fitting 50 in accordance with the present invention. The fitting 50 includes distal end portion 51 having a protrusion 54 extending therefrom, the protrusion forming a proximal end portion 52. The protrusion further includes a skive or relieved area 53 formed adjacent to the distal end portion. An aperture 55 is formed axially within the distal end portion 51, wherein the aperture 55 is in  
10 communication with the skive 53. As described above, the end portion of the distal end 51 is configured to engage the knot and permit smooth advancement of the knot. The fitting 50 is typically a cylindrical element having a flat or slightly convex or concave front face. In an alternative embodiment, the face may be disposed at an angle relative to the axis of the shaft. The distal end 51 of fitting 50 preferably has a diameter equal to or less than the diameter of the  
15 shaft.

Referring now to Figure 5 there is shown a cross sectional view of the shaft assembly 21 in accordance with the present invention. As shown, the shaft assembly comprises the outer shaft 20, the cutting member 60, and the protrusion 54 of the fitting 50. Although the elements are shown and described as being co-axially arranged, it is contemplated that the elements may  
20 be disposed in any manner within the outer sheath. Furthermore, it is contemplated that the outer sheath may be embodied having different geometric shapes such as oval, square, or generally circular as shown.

Referring now to Figure 6, there is shown a suture snare in accordance with the present invention. The suture snare comprises a housing and a snare extending therefrom. As shown in  
25 Figures 1 and 6, the housing 92 has a proximal end and a distal end and is configured to be detachably attached to the shaft 20 of the suture trimmer 10. The snare 95 extends from the distal end of the housing 92. As shown the distal tip portion of the snare 95 is configured having a diamond shape, though many other geometric shapes may be utilized and the use of a diamond shaped distal tip shall be considered exemplary. The snare may be constructed of materials such  
30 as metal or plastic. Examples of suitable metals are stainless steel, copper, steel, titanium, platinum or nickel-titanium. Alternatively, a non-bio-compatible material may be utilized wherein the non bio-compatible material is then coated with a bio-compatible coating such as gold or silver. Examples of plastics that may be utilized are PVC, polyurethane, and similar plastics. In a preferred embodiment the snare is constructed of nickel-titanium wire. The use of  
35 nickel-titanium enables a larger distal end portion 92 than if conventional materials are utilized. Furthermore, the nickel-titanium will not deform or become deformed in normal use because of the shape memory characteristics of the material. The use of a larger distal section on the snare provides for easier loading of the sutures therein.

5 Referring now to Figures 7-10 there is shown the suture trimmer 10 in accordance with the present invention in use. As shown in Figure 7, a suture loop including a knot has been formed in a vessel wall of a patient, the vessel wall having an opening, or arteriotomy, as a result of a medical procedure, for example. The two free ends of the suture are placed within the distal end portion 95 of the suture snare 90, wherein the distal end 95 of the snare has been disposed  
10 through the skive 23 and the aperture 55. The housing 92 being detachably mounted to the shaft 20 of the suture trimmer is removed from the shaft 20 and using a free hand the distal end of the snare 95 is drawn through the aperture 55 and the skive 23. As the snare is drawn through aperture and skive, the free ends of the suture S are additionally drawn through as shown in Figure 8.

15 Referring now to Figure 9 there is shown the end portion of the fitting contacting the knot K, wherein the knot is then advanced to the wound. One free end of the suture S is held tight to withdraw slack from the suture loop. The end portion of the fitting is utilized to place the knot tightly against the tissue, after the knot has been placed, the second free end of the suture S' is tensioned, thereby locking the knot.

20 Referring now to Figure 10, the two free ends of the suture S and S' are taken into a free hand, the proximal end of the cutting member actuating device 40 is pressed, thereby pivoting the actuating device about the pivot pins. The surgeon then applies a force to the distal end of the actuating device. The applied force is transmitted through the actuating device to advance the cutting member from a retracted position within the shaft to an extended position as shown.  
25 The two free ends of the suture are then severed by the sharpened distal tip 61 of the cutting member 60 when the distal tip 61 of the cutting member contacts the fitting 50 distal the opening 23. The suture trimmer and the excess suture is then withdrawn from the tissue path, sheath, or cannula thereby leaving a suture loop having a knot and shortened suture tips extending from the knots. It is contemplated that the trimmed suture tail will have a length of about 1mm to about  
30 10mm, more preferably between about 3mm and about 7mm is preferred to minimize the risks associated with lengths of suture that remain within the body as described above.

Although the present invention has been described in considerable detail with reference to certain preferred embodiments, it is contemplated that one skilled in the art may make modifications to the device herein without departing from the scope of the invention. Therefore,  
35 the scope of the appended claims should not be considered limited to the embodiments described herein

5

**CLAIMS**

1. A suture trimmer, the suture trimmer comprising:  
a shaft having a first end, a second end and a bore extending axially therebetween, the shaft having an opening formed in a side adjacent the distal end;  
10 a fitting on the distal end of the shaft, the fitting having an aperture formed therethrough, the aperture axially aligned with the bore of the lumen and in communication with the opening formed in the shaft; and  
an actuating device in communication with a cutting member slidably disposed within the bore of the shaft, the cutting member configured to be moved between a first position and a  
15 second position, when disposed in the second position the cutting member closes the opening formed in the side of the shaft.
2. The suture trimmer according to Claim 1, further comprising a biasing device the biasing device is coupled to the cutting member, wherein the biasing device retains the cutting  
20 member in the first position.
3. The suture trimmer according to Claim 1, further including a suture snare disposed through the opening and the aperture, the suture snare configured to receive at least one suture.  
25
4. The suture trimmer according to Claim 3, wherein the suture snare is constructed of a material chosen from the group consisting of, stainless steel, nickel-titanium, titanium, steel, and plastics.

- 5            5.        The suture trimmer according to Claim 1, wherein the shaft is constructed of a material chosen from the group consisting of, aluminum, steel, stainless steel, titanium, nickel-titanium, or plastics.
- 10           6.        The suture trimmer according to Claim 1, wherein the fitting disposed on the distal end of the shaft further includes a protrusion, the protrusion extending through the bore of the shaft and connected to the housing.
- 15           7.        The suture trimmer according to Claim 3, wherein the snare is configured to receive at least one suture and draw the suture through the aperture formed in the fitting.
8.        The suture trimmer according to Claim 1, wherein the distal end of the cutting member includes a sharpened edge configured to cut a suture passed through the aperture of the fitting and through the opening formed in the shaft.
- 20           9.        The suture trimmer according to Claim 1, wherein the cutting member is constructed of a material chosen from the group consisting of, aluminum, steel, stainless steel, carbide, titanium, and plastics.
- 25           10.       The suture trimmer according to Claim 1, wherein the aperture formed within the fitting is configured to receive at least one suture therethrough, and the distal end of the fitting is configured to receive and advance at least one knot formed with the suture.
11.       The suture trimmer according to Claim 1, wherein the shaft and fitting are configured to be received within an incision formed in a patient through a lumen.

5

12. A method for closing a suture loop, the method comprising:

tensioning a suture loop, the suture loop disposed within a patient and having two free ends and a knot disposed on one of the free ends;

disposing the two free ends of the suture through a suture trimming device;

10       advancing a distal end of the suture trimming device to contact the knot and advance the knot to close the suture loop while holding at least one end of the suture; and

activating a cutting member operatively associated with the suture trimmer to cut the two free ends of the suture adjacent to the knot.

15       13. The method according to Claim 12, wherein the suture trimmer comprises, a shaft having a first end, a second end and a bore extending axially therebetween, the shaft having an opening formed in a side adjacent the distal end, a fitting on the distal end of the shaft, the fitting having an aperture formed therethrough, the aperture axially aligned with the bore of the lumen and in communication with the opening formed in the shaft, a actuating device coupled to a  
20       cutting member slidably disposed within the bore of the shaft, the cutting member configured to be moved between a first position and a second position, when disposed in the second position the cutting member closes the opening formed in the side of the shaft.

14. The method according to Claim 13, wherein advancing the distal end of the suture  
25       trimmer comprises advancing the distal end of the suture trimmer through a tissue tract toward the suture loop anchored in a tissue wall.

15. The method according to Claim 14, wherein advancing the distal end of the suture trimmer comprises advancing the distal end of the suture trimmer over the two free ends of the

5 suture while the two free ends of the suture extend through an opening formed in the side wall of the suture trimmer and extend outward through a sheath disposed in the tissue tract.

16. The method according to Claim 15, wherein the disposing the two free suture ends of the suture through the suture trimming device comprises disposing the two free ends of the suture through a suture snare and advancing the suture snare through the opening and the  
10 aperture of the suture trimmer.


17. The method according to Claim 12, wherein advancing the distal end of the suture trimming device comprises advancing a square knot.

15 18. The method according to Claim 12, wherein the knot comprises at least one square of knot formed with the suture.


19. The method according to Claim 18, wherein the knot comprises at least two knots disposed adjacent to one another.  
20

20. The method according to Claim 19, wherein tensioning a suture loop comprises grasping a free end of one of the two suture ends in one hand.


21. The method according to Claim 12, wherein the knot comprises at least one clinch  
25 knot formed with the suture.






2/8









4/8




5/8




6/8



7/8



8/8



# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 02/39151

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 A61B17/04

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 00 69342 A (SUTURA, INC.) 23 November 2000 (2000-11-23) the whole document	1,3-5,7, 9-11
A	US 5 242 459 A (BUELNA) 7 September 1993 (1993-09-07) abstract; figures	1,2,8
A	US 5 643 289 A (SAUER ET AL.) 1 July 1997 (1997-07-01) abstract; figures	1
A	WO 94 08515 A (LI MEDICAL TECHNOLOGIES, INC.) 28 April 1994 (1994-04-28) figures	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

\* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*G\* document member of the same patent family

Date of the actual completion of the international search

19 March 2003

Date of mailing of the international search report

26/03/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Giménez Burgos, R

# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US 02/39151

## Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.: 12-21  
because they relate to subject matter not required to be searched by this Authority, namely:  
Rule 39.1(iv) PCT - Method for treatment of the human or animal body by surgery
2. ☐ Claims Nos.:  
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:  
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

## Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

### Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.



# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/US 02/39151

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
WO 0069342	A	23-11-2000	AU	4849500 A	05-12-2000
			EP	1199988 A2	02-05-2002
			JP	2002543910 T	24-12-2002
			WO	0069342 A2	23-11-2000
US 5242459	A	07-09-1993	AU	4992193 A	31-01-1994
			WO	9401045 A1	20-01-1994
US 5643289	A	01-07-1997	CA	2141911 A1	25-08-1995
			DE	69512447 D1	04-11-1999
			DE	69512447 T2	31-05-2000
			EP	0669103 A1	30-08-1995
			US	5669917 A	23-09-1997
WO 9408515	A	28-04-1994	AU	5356894 A	09-05-1994
			WO	9408515 A1	28-04-1994
			US	5439470 A	08-08-1995